

# TOOL SPRAY

## 70-03

**Metaflux®**  
Technical Data Sheet

### DESCRIPTION:

Cooling and lubricating agents combined with mineral oils and synthetic additives. Highly recommended for hastaloid steel. Totally synthetic combinations of cutting oils, contains special ingredients that only evaporates with oxygen contact. The evaporation process brings a cooling effect that absorbs most of the heat that occurs when the parts are cutted, drilled or machined.

Metal drilling: can be sprayed directly onto the drill or on the surface to be drilled. Saw blade: spray along the cutting edge. Internal pipe threads: cutting spray adheres to the surface. Flammable. Follow label instructions. The cutting spray increases the speed of cutting and drilling with no discoloration of stainless steel, aluminium and copper parts when used.

## Economic – Functional - Efficient

### STORAGE RECOMMENDATIONS:

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash hands/nails/face thoroughly after handling. Wear gloves/protective clothing/eye protection/face protection. Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials. Keep containers closed when not in use. Empty containers are always dangerous

### PROPERTIES AND ADVANTAGES:

- Excellent adhesion on curved or rounded surfaces.
- Exempt of nitrite and aggressive agents.
- Doesn't leave any bad odours and isn't dangerous for the skin.
- **Capacity increases; life of the drill up to 100% and saw blades up to 40%.**
- Highly accurate – no over spray, universal applications (one product for all use).
- Cool the parts and absorbs the heat very fast.

Content	Type	Art.-No	Box
400ML.	AEROSOL	70-03	12
100g.	PASTE	71-03	12



1392, Avenue de la gare Mascouche (QC) Canada, J7K 2Z2

1-(888) 452-6382 (450) 477-3102 1-(450) 477-6664

www.ametasolution.com info@ametasolution.com

