ANTI-SPATTER SPRAY

70-04



DESCRIPTION:

Protective spray for gas welding. Special separation agent for plastic processing. The Anti-Spatter spray prevents the adhesion of weld spatter on treated parts. Prevents the fixation of spatter on gas welding nozzles and on nozzle for M.I.G. welding stations.

Apply a thin & even layer on the surfaces to be welded. Nozzles: spray from time to time the gas nozzle, after disconnecting the semi-automatic welding station. In the plastics industry, spray 70-04 on templates when manufacturing polystyrene, polycarbonate or ABS material parts, to prevent damage to shapes or templates by muriatic acid. 70-04 does not interfere with the printing or possible sticking of labels to plastic parts.

STORAGE RECOMMENDATIONS:

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash hands/nails/face thoroughly after handling. Wear gloves/protective clothing/eye protection/face protection. Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials. Keep containers closed when not in use. Empty containers are always dangerous

PROPERTIES AND ADVANTAGES:

- Neutral product, no reaction on the sprayed surface.
- Can be easily removed with warm water.
- Concentrated product non-diluted; economic at use.
- Free from fluorocarbons and silicone oils.
- Contains a foam indicator
- 98% of active product.

Content	Туре	ArtNo	Вох
400ML.	AEROSOL	70-04	12
41./201./2051.	VRAC	75-04	12



