

TORSION SPRAY

70-06

Metaflux®

Technical Data Sheet

DESCRIPTION:

Fully synthetic with great adherence. Especially made for machinery in open or in humid conditions: car, garages, farms, construction yards, industries and machinery maintenances. The long spray tube allows no direct contact on hands kept at a safe distance from moving parts during application.

USE DIRECTIVES:

Apply directly on the belt in action in the gearing system. The Belt Spray can be applied on the inferior face of the belt as well. For the first application, spray a thin film on the entire belt. To maintain a better performance of the belt, repeat the process frequently. Flammable. Follow label instructions.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash hands/nails/face thoroughly after handling. Wear gloves/protective clothing/eye protection/face protection. Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials. Keep containers closed when not in use. Empty containers are always dangerous

PROPERTIES AND ADVANTAGES:

- Eases the softness of surfaces and eliminates sliding or squeaking.
- Increases belt adherence and transmission performances, especially when started.
- Doesn't contain tar or resins. Dust and dirt repellent.
- Keeps belts supple and prevents premature aging.
- Increases the performance up to 50%.
- Increases servicing intervals and durability of belts up to 100%.



Content	Type	Art.-No	Box
400ML	AEROSOL	70-06	12

1392, Avenue de la gare Mascouche (QC) Canada, J7K 2Z2

1-(888) 452-6382 (450) 477-3102 1-(450) 477-6664

www.ametasolution.com info@ametasolution.com



AMETA
SOLUTION.COM