

ADHESIVE SPRAY

70-11

Metaflux®

Technical Data Sheet

DESCRIPTION:

Clear synthetic glue, ideal for bonding large surfaces. METAFLEX synthetic glue is suitable for bonding: Paper, photos, cardboard, textiles, velvet, leather, cork, carpet, glass wool, polystyrene, reproductions, metallic films, rigid polyurethane foam, polystyrene foam on metal, wood, chipboard, particle board, concrete, etc.

USE DIRECTIVES:

The use of an adjustable Vario valve makes it possible, depending on the positioning of the valve, to adjust the power of the flow in a linear fashion; between the "L" markings at the weakest and "H" at the strongest. By rotating the insert located on the valve, it is possible to opt for a vertical or horizontal fan jet. Shake the aerosol well before use. The surfaces to be glued must be clean, dry and perfectly degreased. Spray on both sides to be glued evenly and thinly at about 25 cm. Leave to dry for at least 10 minutes and then assemble the two parts by pressing them together. For short-term assemblies, spray only on one side and let dry twenty minutes before assembling. The assembly can then be undone very easily. To prevent the valve from clogging, purge the aerosol upside down until all gas comes out.

Pressurized container: protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash hands/nails/face thoroughly after handling. Wear gloves/protective clothing/eye protection/face protection. Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials. Keep containers closed when not in use. Empty containers are always dangerous.

PROPERTIES AND ADVANTAGES:

- Very fast adhesion.
- Very good adhesive power and strong bonding of the glued parts.
- Insensitive to moisture, water resistant.
- Functional use and proper use.
- Economical in use.
- Adheres securely and quickly to all surfaces; do not cross.
- Ideal for large areas thanks to fan spraying.
- Temperature resistance: -30 °C to + 80 °C, momentarily at 100 °C (max. 1 hour)



Content	Type	Art.-No	Box
400ML	SPRAY	70-11	12

1392, Avenue de la gare Mascouche (QC) Canada, J7K 2Z2

1-(888) 452-6382 (450) 477-3102 1-(450) 477-6664

www.ametasolution.com info@ametasolution.com



AMETA
SOLUTION.COM