

PROTECT SPRAY

70-19

Metaflux®

Technical Data Sheet

DESCRIPTION:

A special transparent coating for metal surfaces. Fluid and transparent varnish used to protect different type of metallic surface like our [Liquid Aluminium \(product no. 70-16\)](#). Protects all electronic components or printed circuits. Makes the metallic surface more natural by reducing the shine. The fixing of ALU LIQUID SPRAY is reinforced and the superposition of PROTECT-SPRAY METAFLUX ref. 70-19 gives it an indelible character. Protects and insulates: Metals and metallic surfaces as well as any flat surface. Wheel covers, electronic boards, coils and printed and electronic circuits.

USE DIRECTIVES:

[Eliminate all oil, rust and dirt from surfaces with Metaflux 70-15](#). Shake well and spray a thin layer on the part to be treated from a distance of 20-40 cm. Let dry. Apply a second layer if needed. Parts touched by mistake can be cleaned with [citrus cleaner 75-17](#).

Pressurized container: protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash hands/nails/face thoroughly after handling. Wear gloves/protective clothing/eye protection/face protection. Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials. Keep containers closed when not in use. Empty containers are always dangerous.

PROPERTIES AND ADVANTAGES:

- Transparent coating.
- Provides a particularly smooth surface.
- Protects surfaces against dust and moisture.
- Prevents the catching of impurities.
- Keeps its elasticity.
- Remains transparent even when exposed to heat or in the presence of ultraviolet rays.
- Does not interfere with the thermal diffusion characteristics of the treated parts.
- Economical product thanks to its great fluidity.
- Temperature resistance Up to 100 °C
- Cover Up to 30 m²



Content	Type	Art.-No	Box
400ML	SPRAY	70-19	12

1392, Avenue de la gare Mascouche (QC) Canada, J7K 2Z2

✉ 1-(888) 452-6382 ✉ (450) 477-3102 📠 1-(450) 477-6664

🌐 www.ametasolution.com ✉ info@ametasolution.com



AMETA
SOLUTION.COM