

PROTECTION WAX SPRAY

70-39

Metaflux®

Technical Data Sheet

DESCRIPTION:

Corrosion protection **coating wax** for metal surfaces to be simply sprayed on. A good adhesion for all metals in inaccessible panel sections, tools, moulds, machine parts to be stored or transported overseas. Permanently elastic protective film for metallic surfaces. Car body panel protection, longer storage of moulds and tools, From machines, cavities and much, much more....

USE DIRECTIVES:

Eliminate all oil, rust and dirt from surfaces with Metaflux 70-15.

Shake the aerosol well and spray about 25 cm from the parts to be protected. In extreme conditions, apply a few coatings. Allow drying between applications (Approx. 70 minutes). Can easily be removed with [Metaflux 75-17 Spray](#)

Pressurized container: protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash hands/nails/face thoroughly after handling. Wear gloves/protective clothing/eye protection/face protection. Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials. Keep containers closed when not in use. Empty containers are always dangerous.

PROPERTIES AND ADVANTAGES:

- Totally synthetic and long lasting protection.
- Water suppressant with capillary effect.
- Good adhesion to all metals.
- Long-term protection against corrosive influences (physical & atmospheric) for all metallic surfaces
- Permanently elastic protective film
- Water-pushing
- Very good adhesion to all metals
- Removable with METAFLUX 75-17 Citrus cleaner.



Content	Type	Art.-No	Box
400ML	SPRAY	70-49	12

1392, Avenue de la gare Mascouche (QC) Canada, J7K 2Z2

✍ 1-(888) 452-6382 ✍ (450) 477-3102 📠 1-(450) 477-6664

🌐 www.ametasolution.com ✉ info@ametasolution.com



AMETA
SOLUTION.COM