ZINC BASE SPRAY

70-46



DESCRIPTION:

Coating spray for anti-corrosion protection to ferrous base metals. Cathodic corrosion protection, zinc grey, especially for the zinc coating of parts for interior use and as a primer before painting, fast drying. The economical solution for all painted parts.

USE DIRECTIVES:

<u>Eliminate all oil, rust and dirt from surfaces with Metaflux 70-15.</u> Spray onto clean and dry surfaces at room temperature. Blank parts need no pre-treatment, burn marks should be cleaned with a wire brush. The temperature of the metal surface to be treated should not be higher than 40C, higher temperatures could affect the primer. Flammable.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat/sparks/open flames/hot sur-

faces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash hands/nails/face thoroughly after handling. Wear gloves/protective clothing/eye protection/face protection. Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials. Keep containers closed when not in use. Empty containers are always dangerous.

PROPERTIES AND ADVANTAGES:

- · Made of 99.5% pure zinc
- · Quick drying.
- · Easy to apply
- Strong adherence.
- Heat resistant up to 140oC.
- · Water insolvable.
- An aerosol can cover up to 8 m². (Taking thickness layer in consideration)

Content	Туре	ArtNo	Вох
400ML.	AEROSOL	70-46	12





