SAFETY DATA SHEET (SDS)

Section 1. Identification

Product identifier	Metaflux 70-55 Care Fluid for Stainless Steel
Other means of identification	70-55
Recommended use and restrictions on use	LUBRICANT/AEROSOL
Initial supplier identifier	AMETA SOLUTION.COM 1392, AVENUE DE LA GARE, MASCOUCHE, (QUEBEC), J7K 2Z2, CANADA TEL. (450) 477-3102 & (888) 452-6382 WWW.AMETASOLUTION.COM
Emergency telephone number/restriction on use	Canada – CANUTEC 24 hour number 613-996-6666

Section 2. Hazard identification

Classification of hazardous product (name of the category or subcategory of the hazard class)

Extremely flammable aerosol (Category 1)
Aspiration hazard (Category 1)
Eye irritation (Category 2A)
Specific target organ toxicity – single exposure (Category 3), Central nervous system

Information elements (symbols, signal words, hazard statements and precautionary statements of the category/subcategory)

Danger
H222 Extremely flammable aerosol.
H229 Pressurized container: may burst if heated.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
*** May displace oxygen and cause rapid suffocation. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash hands/nails/face thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear gloves/protective clothing/eye protection/face protection. P305 + P351 + P338 IF IN EYES, Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical attention. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a doctor if you feel unwell. P301+P310 IF SWALLOWED: Immediately call a doctor. P331 DO NOT INDUCE VOMITING. P410+P412+P403 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated area. P233 Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other hazards known	Simple Asphyxiants (Category 1) A gas that is a simple asphyxiant***

Section 3. Composition/information on ingredients

Chemical name (common name/synonyms)	**CAS number or other**	**Concentration (%)***
Isopropanol	67-63-0	60-80
Butane	106-97-8	30-60
White mineral oil (petroleum)	8042-47-5	10-30
Propane	74-98-6	5-10
Isobutane	75-28-5	5-10
Dodecanol-1 ethoxylated	9002-92-0	< 3

All ingredients are listed according to OSHA (29 CFR).
* Statement - This safety data sheet provides concentration range(s) instead of the actual concentration(s) by weight (except for gases/propellants by volume) considered trade secret(s).

Section 4. First-aid measures

Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
Ingestion	IF SWALLOWED: Immediately call a doctor. DO NOT INDUCE VOMITING. NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Rinse mouth thoroughly with water. Have victim drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.
Skin contact	IF ON SKIN, Wash with plenty of water for several minutes (5-10). If skin irritation occurs: Get medical attention.
Eye contact	IF IN EYES, Rinse cautiously with water for several minutes (15-20). Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Most important symptoms and effects (acute or delayed)	Causes serious eye irritation.
Indication of immediate medical attention/special treatment	In all cases, call a doctor. Do not forget this document.

Section 5. Fire-fighting measures

Specific hazards of the hazardous product (hazardous combustion products)

Carbon oxides and other irritant/toxic gases and fumes.

Suitable and unsuitable extinguishing media

In case of fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish.

Special protective equipment and precautions for fire-fighters

During a fire, irritating/toxic smoke and fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece. Shield personnel to protect from venting, rupturing or bursting cans. Move containers from fire area if it can be done without risk. Water spray may be useful in cooling equipment and cans exposed to heat and flame.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment (See Section 8).

Methods and materials for containment and cleaning up

Avoid release to the environment. Collect spillage. Ventilate area of release. Stop the leak if it can be done safely. Contain and absorb any spilled liquid concentrate with inert absorbent material, then place material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.

Section 7. Handling and storage

Precautions for safe handling

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.
Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to Section 8.

Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks.

Section 8. Exposure controls/Personal protection

Control parameters (biological limit values or exposure limit values and source of those values)

Exposure limits: CAS 74-98-6 & 75-28-5 & 106-97-8 – ACGIH – TLV-TWA (STEL) and/or PEL-TWA 1000 ppm; CAS 67-63-0 – ACGIH – TLV-TWA 200 ppm & TLV-STEL 400 ppm & PEL-TWA 400 ppm;

Appropriate engineering controls

Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Individual protection measures/personal protective equipment

Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits are unknown. Chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact, must be worn during all handling operations. Wear protective chemical splash goggles to prevent mists from entering the eyes. Wash hands/nails/face thoroughly after handling. Do not eat, drink or smoke when using this product. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use.

Section 9. Physical and chemical properties

Physical state	Aerosol/Liquid	**pH**	Not available
Colour	Clear	**Kinematic viscosity**	Not available
Odour	Characteristic	**Solubility**	Insoluble
Melting/freezing point	Not available	**Partition coefficient - n-octanol/water (log)**	Not available
Initial boiling point/ initial/range	Not available	**Vapour pressure**	Not available
Flammability	Extremely flammable aerosol	**Density/relative density**	0.695 g/cm^3 @ 20ºC
Upper and lower flammability/explosive limits	1.5 % - 12.0 %	**Relative vapour density**	Heavier than air
Flash point	Not available	**Particle characteristics**	Not available
Auto-ignition temperature	365ºC	**VOC**	Not available
Decomposition temperature	Not available	**Other**	None known

Section 10. Stability and reactivity

Reactivity

Does not react under the recommended storage and handling conditions prescribed.

Chemical stability

Stable under the recommended storage and handling conditions prescribed.

Possibility of hazardous reactions

Accumulation of flammable if product is heated. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Conditions to avoid (static discharge, shock or vibration)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Incompatible materials

Oxidizing materials; etc.

Hazardous decomposition products

None known

Section 11. Toxicological information

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact)

May be fatal if swallowed and enters airways. May displace oxygen and cause rapid suffocation. Causes serious eye irritation. May cause drowsiness or dizziness.

Symptoms related to the physical, chemical and toxicological characteristics

Respiratory tract irritation, coughing, shortness of breath, dizziness, drowsiness, nausea and headaches.

Delayed and immediate effects (chronic effects from short-term and long-term exposure)

Skin Sensitization – No data available;
Respiratory Sensitization – No data available;
Germ Cell Mutagenicity – No data available;
Carcinogenicity – No ingredient listed by IARC, ACGIH, NTP or OSHA;
Reproductive Toxicity – No data available;
Specific Target Organ Toxicity — Single Exposure – No data available;
Specific Target Organ Toxicity — Repeated Exposure – No data available;
Aspiration Hazard – Possible;
Health Hazards Not Otherwise Classified – No data available.

Numerical measures of toxicity (ATE; LD_{50} & LC_{50})

CAS 75-28-5 & 106-97-8 LC_{50} 658000 mg/m^3 4 hrs (rat); CAS 67-63-0 LD_{50} Oral - Rat - 4720 mg/kg; LC_{50} Inhalation - Rat - 17000 ppm 4hrs; LD_{50} Dermal - Rabbit - 12890 mg/kg;
ATE not available in this document.

Section 12. Ecological information

Ecotoxicity (aquatic and terrestrial information)	No data available for this product.
Persistence and degradability	No data available for this product.
Bioaccumulative potential	No data available for this product.
Mobility in soil	No data available for this product.
Other adverse effects	No data available for this product.

Section 13. Disposal considerations

Information on safe handling for disposal/methods of disposal/contaminated packaging

Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Section 14. Transport information

UN number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations

UN1950; AEROSOLS; CLASS 2.1

UN number; Proper shipping name; Class(es); Packing group (PG) of the 49 CFR (USA)

UN1950; AEROSOLS; CLASS 2.1

UN number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime)

UN1950; AEROSOLS; CLASS 2.1

UN number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air)

UN1950; AEROSOLS, FLAMMABLE; CLASS 2.1

Special precautions (transport/conveyance)	May also be shipped as a LIMITED QUANTITY in accordance with TDG.
Environmental hazards (IMDG or other)	None

Section 15. Regulatory information

Safety/health Canadian regulations specifics	Refer to Section 2 for the appropriate classification. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and of the United States OSHA (29 CFR).
Environmental Canadian regulations specifics	Refer to Section 3 for ingredient(s) of the DSL

Safety/health/environmental outside regulations specifics

United States OSHA information: This product is regulated according to OSHA (29 CFR).
United States EPA (Environmental Protection Agency) information: 40 CFR Refer to the ingredients listed in Section 3 & Sections 12; 13 & 14.
United States TCSA information: Refer to the ingredients listed in Section 3.
National Fire Protection Association (NFPA):
HEALTH: 1 FLAMMABILITY: 4 INSTABILITY: 1 SPECIAL HAZARDS: Refer to Section 2 & 3.
HAZARD SCALE: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe
California Proposition 65: No ingredient known to the State of California to cause cancer or other reproductive harm.

Section 16. Other information

Date of the latest revision of the safety data sheet	October 02, 2023 version 2 (NSS ENTREPRISE INC.)
Corrections	Section 2; 3; 9; 14;
References	Safety Data Sheets from manufacturer/supplier & from Canadian Centre for Occupational Health and Safety, CCOHS.

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
ATE	Acute toxicity estimate
CAS	Chemical Abstract Service
DSL	Domestic Substance List
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods Code
LC	Lethal concentration
LD	Lethal Dosage
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program (U.S.A.)
OSHA	Occupational Safety and Health Administration (U.S.A.)
PEL	Permissible Exposure Limit
STEL	Short-term Exposure Limit
TDG	Transport of dangerous goods in Canada
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
WHMIS	Workplace Hazardous Materials Information System

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.