

BRASS SPRAY

70-58

Metaflux®
Technical Data Sheet

DESCRIPTION:

Metallic coating for all solid surfaces. This product is not paint. The Brass Spray is a combination of pure brass and acrylic resin which contains 67% of brass on a dry sheet.

USE DIRECTIVES:

Eliminate all oil, rust and dirt from surfaces with Metaflux 70-15. Parts already painted or varnished in good condition can be sprayed. The spray can be applied on all clean metallic surfaces. Shake well before use.

Pressurized container: protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash hands/nails/face thoroughly after handling. Wear gloves/protective clothing/eye protection/face protection. Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials. Keep containers closed when not in use. Empty containers are always dangerous.

PROPERTIES AND ADVANTAGES:

- Good adherence.
- Quick dry (6 to 8 minutes before touching).
- Does not rub off.
- Economical in use.
- Gives a silky surface.



Content	Type	Art.-No	Box
400ML	SPRAY	70-58	12

1392, Avenue de la gare Mascouche (QC) Canada, J7K 2Z2

✉ 1-(888) 452-6382 ✉ (450) 477-3102 📠 1-(450) 477-6664

🌐 www.ametasolution.com ✉ info@ametasolution.com



AMETA
SOLUTION.COM