

Printing date 12.06.2015 Revision: 05.10.2020

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: METAFLUX 70-74 Supralub-Spray
- · Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation Lubricant
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Metatec Ltd Metaflux Building

Fitzherbert Rd. Portsmouth PO6 1RU

ind@metatec.limited www.metateconline.com

Further information obtainable from: Sales Department

++44 2392 381382

Emergency telephone number: Central Phone Number

++44 2392 381382

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222 Extremely flammable aerosol.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



F+; Extremely flammable

R12: Extremely flammable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard statements

H222 Extremely flammable aerosol.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 2)

Printing date 12.06.2015 Revision: 05.10.2020

Trade name: METAFLUX 70-74 Supralub-Spray

(Contd. of page 1)

P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe spray.

P211 Do not spray on an open flame or other ignition source.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122 °F.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | | | |
|-------------------------|-----------|---|---------|--|
| CAS: 106-97-8 | butane | | 50-100% | |
| EINECS: 203-448-7 | | 🏇 Flam. Gas 1, H220; 🥎 Press. Gas, H280 | | |
| | propane | ♦ F+ R12 | 10-25% | |
| EINECS: 200-827-9 | | 🏇 Flam. Gas 1, H220; 🔷 Press. Gas, H280 | | |
| CAS: 75-28-5 | isobutane | | 2.5-10% | |
| EINECS: 200-857-2 | | 🏇 Flam. Gas 1, H220; 🥎 Press. Gas, H280 | | |

[·] Regulation (EC) No 648/2004 on detergents / Labelling for contents

aliphatic hydrocarbons ≥ 30%

4 First aid measures

- · Description of first aid measures
- · General information:

Take affected persons out into the fresh air.

Do not leave affected persons unattended.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture Risk of bursting in case of fire heat
- · Advice for firefighters
- · Protective equipment: Wear fully protective suit.
- · Additional information Cool endangered receptacles with water spray.

CD

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

Printing date 12.06.2015 Revision: 05.10.2020

Trade name: METAFLUX 70-74 Supralub-Spray

(Contd. of page 2)

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Particular danger of slipping on leaked/spilled product.

Ensure adequate ventilation

Keep away from ignition sources.

- · Environmental precautions: Do not allow product to reach sewage system or any water course.
- · Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Open and handle receptacle with care.

Keep away from heat and direct sunlight.

Avoid inhalation and contact with the skin and the eyes.

· Information about fire - and explosion protection:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Store away from oxidizing agents.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- · Recommended storage temperature: 15 35°C, max. 50°C
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane

WEL (Great Britain) | Short-term value: 1810 mg/m³, 750 ppm | Long-term value: 1450 mg/m³, 600 ppm | Carc (if more than 0.1% of buta-1.3-diene)

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.
- · Protection of hands:
- · Material of gloves If contamination is possible, use gloves made of nitrile according EN 374

(Contd. on page 4)

Printing date 12.06.2015 Revision: 05.10.2020

Trade name: METAFLUX 70-74 Supralub-Spray

• Penetration time of glove material > 480 min / 0.4 mm thickness

Not determined.

· Eye protection: Not required.

(Contd. of page 3)

9 Physical and chemical properties

| . In | formation | on basia | nhwa | ical and | laham | iaal . | manantias |
|-------|-----------|----------|-------|----------|--------|--------|-----------|
| · 111 | ıormanon | on vasic | DILVS | ıcaı ana | ı cnem | ıcaı t | roverues |

· General Information

· Appearance:

· pH-value:

Form: Aerosol
Colour: Colourless
Odour: Recognizable
Odour threshold: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: -44°C

• Flash point: Not applicable, as aerosol.

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 365°C

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

• Danger of explosion: Risk of bursting at temperatures > 50 °C. Damage of the container may lead

to the formation of explosive mixtures of gas/vapors with air.

· Explosion limits:

 Lower:
 1.5 Vol %

 Upper:
 10.9 Vol %

 Pressure (20°C)
 3,0 - 5,0 bar

• Density at 20°C: 0.633 g/cm^3

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Solvent content:

Organic solvents: 0.0 % VOC (EC) 30 %

442,5 g/l = 0,177 kg/400 ml

· Other information No further relevant information available.

· Additional information Vapors are heavier than air.

10 Stability and reactivity

- $\cdot \textit{Reactivity}$
- · Chemical stability
- Thermal decomposition / conditions to be avoided: Risk of bursting at temperatures >50°C.
- · Possibility of hazardous reactions

By use or incidental release the formation of explosive vapor/air mixtures is possible.

- · Conditions to avoid Temperatures >50°C
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 5)

Printing date 12.06.2015 Revision: 05.10.2020

Trade name: METAFLUX 70-74 Supralub-Spray

· Additional information: Stable for a storage time of min. 24 months

(Contd. of page 4)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

12 Ecological information

- · Toxicity
- · Acquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- $\cdot \textit{Bioaccumulative potential No further relevant information available}.$
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Generally not hazardous for water
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

empty cans: material recycling

filled cans: remove in accordance with local regulations

| · European waste catalogue | | | | |
|----------------------------|---|--|--|--|
| 16 00 00 | WASTES NOT OTHERWISE SPECIFIED IN THE LIST | | | |
| 16 05 00 | gases in pressure containers and discarded chemicals | | | |
| 16 05 04* | gases in pressure containers (including halons) containing dangerous substances | | | |

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

| UN | ·Nun | ıber |
|----|------|------|

· ADR, IMDG, IATA UN1950

· UN proper shipping name

· ADR 1950 AEROSOLS
· IMDG AEROSOLS

· IATA AEROSOLS, flammable

(Contd. on page 6)

Printing date 12.06.2015 Revision: 05.10.2020

Trade name: METAFLUX 70-74 Supralub-Spray

(Contd. of page 5) · Transport hazard class(es) $\cdot ADR$ · Class 2 5F Gases. · Label 2.1 · IMDG, IATA 2.1 · Class \cdot Label 2.1 · Packing group Void · ADR, IMDG, IATA · Environmental hazards: No · Marine pollutant: Warning: Gases. · Special precautions for user · Danger code (Kemler): F-D,S-U· EMS Number: · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: \cdot ADR · Limited quantities (LQ) 1L· Transport category 2 D· Tunnel restriction code · Remarks: Transportation as "LIMITED QUANTITIES" (LQ2) according 3.4 ADR possible. Sole marking: Sign for "Limited Quantities" (rhombus with two black edges) Entry in the transportation document: Transportation according chapter 3.4 ADR UN1950, AEROSOLS, 2.1 · UN "Model Regulation":

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

GI

Printing date 12.06.2015 Revision: 05.10.2020

Trade name: METAFLUX 70-74 Supralub-Spray

(Contd. of page 6)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

R12 Extremely flammable.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

VOC: Volatile Organic Compounds (USA, EU)

GE