

Multi-TS

75-04

Technical Data Sheet

Description:

Anti-spatter fluid that prevents adhesion of weld spatter. It protects the work piece, the welding nozzle and the welding equipment. Silicone and solvent-free. Non-flammable.

Use directions

Spray a very thin and even layer (fog) with a hand sprayer, a light coat on the parts to be protected. Before continuing machining, wipe the Multi-TS or rinse with water. Before painting, it is recommended to degrease the undercoat thoroughly with 79-02 (Brake Cleaner). For parts to be galvanized, no preparation is needed.

Metalworking, auto body shops, tank- and boiler-making, servicing, special construction, car construction, crane construction and any welding operations.

Can be used for all welding processes, regardless of the welding method.



Storage recommendations:

Protect from freezing: store at room temperature between 5°C and 40°C.

Protect from sun light: it won't damage the product but the color may change.


Properties and advantages

- With high-temperature resistance.
- Silicone free and no hazardous vapors.
- No solvent, no acids and no solvents.
- Odourless.
- Washes off with clean water.
- Non-flammable.
- Economic in use.
- Can be diluted 1:1



Packaging:



Content	Type	Art.-No	
960 ml [32.46 fl.oz.]	sprayer	75-0404	12
4 l [1.06 gal.]	canister	75-0420	4
20 l [5.28 gal.]	canister	75-0445	1

1392, Avenue de la gare Mascouche (QC) Canada, J7K 2Z2

☎ 1-(888) 452-6382 ☎ (450) 477-3102 ☎ 1-(450) 477-6664

🌐 www.ametasolution.com ✉ info@ametasolution.com



AMETA
SOLUTION.COM