

ANTI-SEIZE SPRAY

70-82

Metaflux®

Technical Data Sheet

DESCRIPTION:

Heavy duty lubricant and separating spray with anti-seize action, resistant to water, oil and many acids and alkalis, pressure up to 3.600 kp/cm², temperature range from -80°C to +1.200°C. Grey assembly product with metallic pigments for protection against seizure and corrosion. Used for: hinders seizure, fretting corrosion and frictional oxidation (bolts, nuts, washers, valve packings, piping connections, link pins, pulleys, etc.); for service and maintenance.

USE DIRECTIVES:

Eliminate all oil, rust and dirt from surfaces with Metaflux 70-15. Shake well before use. Spot-on application thanks to spray-tube.

Pressurized container: protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash hands/nails/face thoroughly after handling. Wear gloves/protective clothing/eye protection/face protection. Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials. Keep containers closed when not in use. Empty containers are always dangerous.

PROPERTIES AND ADVANTAGES:

- Temperature range -80 °C to +1200 °C
- Pressure resistant to 35,300 N/cm² (3600 kp/cm²)
- Free of nickel and copper (no electrolytical attack)
- High resistance to saltwater, organic solvents, and most acids and alkalies
- Particle size (lubricant): 44 µm
- Specific gravity (lubricant): 1.19 g/ml
- Flash point (lubricant): > 300 °C
- NLGI grade (lubricant): 1
- Worked penetration ASTM D-217A (lubricant): 335
- Free of CFCs



Content	Type	Art.-No	Box
400ML	SPRAY	70-82	12

1392, Avenue de la gare Mascouche (QC) Canada, J7K 2Z2

✉ 1-(888) 452-6382 ✉ (450) 477-3102 ☎ 1-(450) 477-6664

🌐 www.ametasolution.com ✉ info@ametasolution.com



AMETA
SOLUTION.COM