

DRI-LUBE SPRAY

70-83

Metaflux®
Technical Data Sheet

DESCRIPTION:

MoS₂-based dry lubricant. All areas where it is imperative to have a dry and clean lubrication, especially for applications where dust and dirt should not adhere to the lubricated areas. Example: flour mill, tile factory, spice factories, cement works ... Long-lasting clean lubricant coating. Does not require frequent renewal. Especially good for slow moving parts or areas of friction.

USE DIRECTIVES:

Eliminate all oil, rust and dirt from surfaces with Metaflux 70-15. Shake well before use. Spray a thin layer over the parts to be lubricated at a distance of 25 cm.

Pressurized container: protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash hands/nails/face thoroughly after handling. Wear gloves/protective clothing/eye protection/face protection. Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials. Keep containers closed when not in use. Empty containers are always dangerous.

PROPERTIES AND ADVANTAGES:

- Withstands temperatures from -120 °C to 460 °C.
- Corrosion protection.
- Very high stability of friction coefficients.
- High resistance to pressure.
- No aging effect; does not become resinous.
- Remains perfectly effective on all surfaces, even when unsolicited over a long period.
- Very good adhesion.
- Fast drying.
- Free of C.F.C.



Content	Type	Art-No	Box
400ML	SPRAY	70-83	12