

# HT-SUPER SPRAY

## 70-84

Metaflux®

Technical Data Sheet

### DESCRIPTION:

Metaflux HT Super Lube Spray is a hi-pressure & hi-cling lubricant that prevents seizing and corrosion. Use on parts subject to; high pressures, vibrations, bumps, and shock - on chains, chain wheels, wire ropes, guiding rails, hinges and joints, hoists, cables, revolving joints etc. For all parts which take high pressures, vibrations bumps, and shock: chains, chain wheels, wire ropes, guiding rails, hinges and joints, hoists, cables, revolving joints etc.

### USE DIRECTIVES:

Eliminate all oil, rust and dirt from surfaces with Metaflux 70-15. Shake well before use. Spray a thin layer over the parts to be lubricated at a distance of 25 cm.

Pressurized container: protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat/sparks/ open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash hands/nails/face thoroughly after handling. Wear gloves/protective clothing/eye protection/face protection. Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials. Keep containers closed when not in use. Empty containers are always dangerous.

### PROPERTIES AND ADVANTAGES:

- High strain resistant lubricant spray
- Prevents seizing and corrosion
- Optimal coverage
- Secure and fast adhesion
- Resistant to saltwater, thinned lye, acids and corrosive industrial environments
- Water repellent
- Light yellow colour
- Temp. resistance: -30°C to +200°C [-22°F to +392°F]
- Thickness: 0.683 g/cm<sup>3</sup> [0.39 oz./in<sup>3</sup>]



Content	Type	Art.-No	Box
400ML	SPRAY	70-84	12

1392, Avenue de la gare Mascouche (QC) Canada, J7K 2Z2

✂ 1-(888) 452-6382 ✂ (450) 477-3102 📠 1-(450) 477-6664

🌐 www.ametasolution.com ✉ info@ametasolution.com



**AMETA**  
SOLUTION.COM

AMETA • Distributeur exclusif de  
Production ISO 9002 • Membre  
Tél.: (450) 477-3102 • Fax: (450) 477-3102