

# HT-SUPER SPRAY

## 70-89

**Metaflux®**  
Technical Data Sheet

### DESCRIPTION:

Colourless high adherence lubricant with high resistance to pressure. Can be used on most parts exposed to high pressure, vibrations and shocks. Ideal for a long lasting lubrication of mechanism exposed to harsh conditions or to water.

### USE DIRECTIVES:

Eliminate all oil, rust and dirt from surfaces with Metaflux 70-15.

Shake the aerosol well and spray about 25 cm from the part to be lubricated.

Pressurized container: protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash hands/nails/face thoroughly after handling. Wear gloves/protective clothing/eye protection/face protection. Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials. Keep containers closed when not in use. Empty containers are always dangerous.

### PROPERTIES AND ADVANTAGES:

- Protect the treated parts from corrosion and jamming
- Very high viscosity and capillarity
- The adherence is almost instantaneous
- Highly resistant to water, sea water, acids, brine and fumes
- Eliminate moisture
- Resist temperatures from -30°C to 200°C



Content	Type	Art.-No	Box
400ML	SPRAY	70-89	12

1392, Avenue de la gare Mascouche (QC) Canada, J7K 2Z2

✍ 1-(888) 452-6382 ✍ (450) 477-3102 📠 1-(450) 477-6664

🌐 [www.ametasolution.com](http://www.ametasolution.com) ✉ [info@ametasolution.com](mailto:info@ametasolution.com)



**AMETA**  
SOLUTION.COM