

**Safety data sheet  
according to Regulation (EC) No 1907/2006, Annex II**

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

**Identification of the substance or preparation**

**Metaflux 70-58 Messing-Spray**

**Use of the substance/preparation**

Coating

**Company/undertaking identification**

METAFLUX AG, Industriestrasse 11, CH-4313 Möhlin  
Telephone +41-61 851 08 00    Telefax +41-61 851 08 08

Distribution U.K./Ireland:  
Metaflux (UK)/Metatec Ltd., Fitzherbert Rd, Portsmouth PO6 1RU  
Tel. 02392-381 382 Fax 02392-380 888

E-mail address of the competent person: info@chemical-check.de, k.schnurbusch@chemical-check.de

**Emergency telephone**

**Advisory office in case of poisoning:**

Canutec: 1-613-996-6666

**2. HAZARDS IDENTIFICATION**

**To people**

See point 11 and 15.  
Preparation is classified as hazardous in the sense of directive 1999/45/EC.  
Product is extremely flammable.  
The following may occur:  
Inhalation of fumes may have narcotic effect.  
Contact with skin can cause irritation.  
When using: development of explosive vapour/air mixture possible.

**To the environment**

See point 12.  
Hydrocarbons can be harmful to water.



**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical name			
content %	Symbol	R-phrases	EINECS, ELINCS
	Registration number (ECHA)	DNEL	PNEC
Xylene			
1 -< 12,5	Xn/Xi	10-20/21-38	215-535-7
CAS 1330-20-7			
Naphtha (petroleum), hydrotreated heavy			
1 - 5	Xn	10-65	265-150-3
CAS 64742-48-9			
Naphtha (petroleum), hydrotreated light			
1 - 10	F/Xn	11-52-53-65	265-151-9
CAS 64742-49-0			



Safety data sheet according to Regulation (EC) No 1907/2006,  
Annex II Revision: 2025-02-24  
Metaflux 70-58 Messing-Spray

Dimethyl ether		Substance for which an EU exposure limit value applies.	
30 - 70	F+	12	204-065-8
CAS 115-10-6			

Naphtha (petroleum), hydrodesulfurized heavy			
1 -< 2,5	Xn/N	10-51-53-65-66-67	265-185-4
CAS 64742-82-1			

Ethylbenzene			
1 -< 5	F/Xn	11-20	202-849-4
CAS 100-41-4			

For complete wording of the R-phrases, refer to point 16.

## 4. FIRST AID MEASURES

### 4.1 Inhalation

Supply person with fresh air and consult doctor according to symptoms.  
Keep Data Sheet available.

### 4.2 Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.  
Keep Data Sheet available.

### 4.3 Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

### 4.4 Ingestion

Do not induce vomiting. Consult doctor immediately.  
Keep Data Sheet available.

### 4.5 Special resources necessary for first aid

n.c.

## 5. FIRE-FIGHTING MEASURES

### 5.1 Suitable extinguishing media

Dry extinguisher  
CO<sub>2</sub>

### 5.2 Extinguishing media which shall not be used for safety reasons

High volume water jet

### 5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

In case of fire the following can develop:

Gases hazardous to health

Danger of explosion by prolonged heating.

### 5.4 Special protective equipment for fire-fighters

Protective respirator with independent air supply

According to size of fire

Full protection, if necessary

### 5.5 Further information

Dispose of contaminated extinction water according to official regulations.

## 6. ACCIDENTAL RELEASE MEASURES

Refer to point 13. and for personal protection refer to point 8.

### 6.1 Personal precautions

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

### 6.2 Environmental precautions

If leakage occurs, dam up.

### 6.3 Methods for cleaning up



Safety data sheet according to Regulation (EC) No 1907/2006,  
Annex II Revision: 2025-02-24  
Metaflux 70-58 Messing-Spray

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Collect using absorbant material (e.g. Universal binding medium), and dispose of according to point 13.

## 7. HANDLING AND STORAGE

### 7.1 Handling

#### Tips for safe handling:

See point 6.1

Observe directions on label and instructions for use.

Keep away from sources of ignition - Do not smoke.

Only use working methods according to operating instructions.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Switch on available suction system.

Ensure good ventilation.

### 7.2. Storage

#### Requirements for storage rooms and containers:

Not to be stored in gangways or stair wells.

Do not store with flammable or self-igniting materials.

Observe regulations for keeping separated.

Store product closed and only in original packing.

Observe special regulations for aerosols.

Observe TRG 300 (German regulation).

#### Special storage conditions:

See point 10

Keep protected from direct sunlight and temperatures over 50°C.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Exposure limit values

	<b>Chemical Name</b>	Xylene	Content %:1 -<	12,5
	WEL-TWA: 50 ppm (220 mg/m3) (WEL), 50 ppm (221 mg/m3) (EC)	WEL-STEL: 100 ppm (441 mg/m3) (WEL), 100 ppm (442 mg/m3) (EC)	---	
	BMGV: 650 mmol methyl hippuric acid/mol creatinine in urine, post shift (Xylene, o-, m-, p- or mixed isomers) (BMGV)	Other information: Sk (WEL)		
	<b>Chemical Name</b>	Naphtha (petroleum), hydrotreated heavy	Content %:1 - 5	
	WEL-TWA: 1200 mg/m3 (normal and branched chain >= C7) (WEL), 600 mg/m3 (AGW)	WEL-STEL: 2(II) (AGW)	---	
	BMGV: ---	Other information: ---		
	<b>Chemical Name</b>	Naphtha (petroleum), hydrotreated light	Content %:1 - 10	
	WEL-TWA: 1200 mg/m3 (normal and branched chain >= C7) (WEL), 600 mg/m3 (AGW)	WEL-STEL: 2(II) (AGW)	---	
	BMGV: ---	Other information: ---		
	<b>Chemical Name</b>	Dimethyl ether	Content %:30 - 70	
	WEL-TWA: 400 ppm (766 mg/m3) (WEL), 1000 ppm (1920 mg/m3) (EC)	WEL-STEL: 500 ppm (958 mg/m3) (WEL)	---	
	BMGV: ---	Other information: ---		
	<b>Chemical Name</b>	Naphtha (petroleum), hydrodesulfurized heavy	Content %:1 -<	2,5
	WEL-TWA: 300 mg/m3 (AGW)	WEL-STEL: 2(II) (AGW)	---	
	BMGV: ---	Other information: ---		
	<b>Chemical Name</b>	Ethylbenzene	Content %:1 -<	5
	WEL-TWA: 100 ppm (441 mg/m3) (WEL), 100 ppm (442 mg/m3) (EC)	WEL-STEL: 125 ppm (552 mg/m3) (WEL), 200 ppm (884 mg/m3) (EC)	---	
	BMGV: ---	Other information: Sk (WEL)		





Safety data sheet according to Regulation (EC) No 1907/2006,  
Annex II Revision: 2025-02-24  
Metaflux 70-58 Messing-Spray

Chemical Name	n-butyl acetate	Content %:
WEL-TWA: 150 ppm (724 mg/m3)	WEL-STEL: 200 ppm (966 mg/m3)	---
BMGV: ---	Other information: ---	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

## 8.2 Exposure controls

### 8.2.1 Occupational exposure controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A (EN 14387)

Hand protection:

Solvent resistant protective gloves (EN 374).

If applicable

Protective nitrile gloves (EN 374)

Eye protection:

If applicable

Tight fitting protective goggles (EN 166) with side protection, with danger of projections.

Skin protection:

Protective working garments (e.g. safety shoes EN 344, long-sleeved protective working garments)

Additional information on hand protection - No tests have been performed.

Selection made for preparations according to the best available knowledge and information on the ingredients.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.2 Environmental exposure controls

n.av.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Aerosol

Substance:

Liquid

Colour:

Brass

Odour:

n.av.

pH-value undiluted:

n.av.

Boiling point/boiling range (°C):

n.av.

Melting point/melting range (°C):

n.av.

Flash point (°C):

n.c.

Flammability (solid, gas):

Yes

Vapour pressure:

3,5-4,5 bar/20°C, 8,5-9,5 bar/50°C

## 10. STABILITY AND REACTIVITY

### Conditions to avoid

See point 7

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

### Materials to avoid

Safety data sheet according to Regulation (EC) No 1907/2006,  
Annex II Revision: 2025-02-24  
Metaflux 70-58 Messing-Spray

See point 7  
Avoid contact with oxidizing agents.  
Avoid contact with other chemicals.

**Hazardous decomposition products**

See point 5.3

**11. TOXICOLOGICAL INFORMATION**

**Acute toxicity and immediate effects**

Ingestion, LD50 rat oral (mg/kg):	n.av.
Inhalation, LC50 rat inhal.(mg/l/4h):	n.av.
Skin contact, LD50 rat dermal (mg/kg):	n.av.
Eye contact:	n.av.

**Delayed and chronic effects**

Sensitization:	n.c.
Carcinogenicity:	n.c.
Mutagenicity:	n.c.
Reproductive toxicity:	n.c.
Narcosis:	Possible

**Further information**

No classification according to calculation procedure.

**12. ECOLOGICAL INFORMATION**

Water hazard class (Germany):	2
Self classification:	Yes (Vw/VwS)
Persistence and degradability:	n.av.
Behaviour in sewage plants:	n.av.
Aquatic toxicity:	n.av.
Ecological toxicity:	n.av.

**13. DISPOSAL CONSIDERATIONS**

**13.1. for the material / preparation / residue**

The waste codes are recommendations based on the scheduled use of this product.  
Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)  
16 05 04 gases in pressure containers (including halons) containing dangerous substances  
Recommendation:  
Pay attention to local and national official regulations  
E.g. dispose at suitable refuse site.

**13.2 for contaminated packing material**

See point 13.1  
Pay attention to local and national official regulations

**14. TRANSPORT INFORMATION**

**General statements**

UN-Number: 1950

**Road/Rail-transport (ADR/RID)**

Class/packing group:	2/-	
UN 1950 AEROSOLS		
Classification code:	5F	
LQ:	2	

**Transport by sea**

IMDG-code:	2.1/-	(class/packing group)	
EmS:	F-D, S-U		
Marine Pollutant:	n.a.		

AEROSOLS

**Transport by air**

IATA: 2.1/-/ (class/secondary danger/packing group)

Aerosols, flammable

**Additional information:**

**Minimum amount regulations have not been taken into account.**

Danger code and packing code on request.

**15. REGULATORY INFORMATION**

**Classification according to Dangerous Product Regulations incl. EC Directives (67/548/EEC and 1999/45/EC)**



Symbols: F+

Indications of danger:

Extremely flammable

R-phrases:

12 Extremely flammable.

Without adequate ventilation, formation of explosive mixtures may be possible.

S-phrases:

9 Keep container in a well-ventilated place.

23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

35 This material and its container must be disposed of in a safe way.

51 Use only in well-ventilated areas.

Additions:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Keep away from sources of ignition - No smoking.

Keep out of the reach of children.

Observe restrictions:

Yes

Observe youth employment law (German regulation).

**16. OTHER INFORMATION**

These details refer to the product as it is delivered.

Storage class VCI (Germany):

2 B

Revised points:

8

The following phrases represent the prescribed R-phrases for the ingredients (designated in point 3).

10 Flammable.

20/21 Harmful by inhalation and in contact with skin.

20/21 Also harmful by inhalation and in contact with skin.

38 Irritating to skin.

65 Harmful: may cause lung damage if swallowed.

65 Also harmful: may cause lung damage if swallowed.

11 Highly flammable.

52 Harmful to aquatic organisms.

53 May cause long-term adverse effects in the aquatic environment.

12 Extremely flammable.

51 Toxic to aquatic organisms.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

20 Harmful by inhalation.

**Legend:**

n.a. = not applicable / n.v., k.D.v. = n.av. = not available / n.g. = n.c. = not checked

WEL = Workplace Exposure Limit EH40, TWA = Long-term exposure limit (8-hour TWA (= time weighted average) reference period), STEL = Short-term exposure limit (15-minute reference period) / BMGV = Biological monitoring guidance value EH40

AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany) / BGW = "Biologischer Grenzwert" (biological limit value, Germany)

VbF = Regulations for flammable liquids (Austria)

WGK = water hazard class (Germany) - WGK 3 = very hazardous, WGK 2 = hazardous, WGK 1 = slightly hazardous to water

VOC = Volatile organic compounds / AOX = Adsorbable organic halogen compounds

VwVwS = Administrative Order relating to substances hazardous to water (Germany)

The statements made here should describe the product with regard to the necessary safety precautions - they are

not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.



Safety data sheet according to Regulation (EC) No 1907/2006,  
Annex II Revision: 2025-02-24  
Metaflux 70-58 Messing-Spray

---

These statements were made by:

Gefahrstoffberatung Schnurbusch GmbH & Co. KG Tel.: 05233-9417-0 FAX: 05233-941790

(c) by Gefahrstoffberatung Schnurbusch GmbH & Co. KG. The copying or changing of this document is forbidden except with consent of the Gefahrstoffberatung Schnurbusch GmbH & Co. KG.