



#### SAFETY DATA SHEET (SDS)

Section 1. Identification		
Product identifier	Metaflux 70-82 Anti-Seize-Spray (Moly-Spray)	
Other means of identification 70-82		
Recommended use and restrictions on use   LUB1		LUBRICANT/AEROSOL
Initial supplier identifier	AMETA SOL	UTION.COM 1392, AVENUE DE LA GARE, MASCOUCHE, (QUEBEC), J7K 2Z2, CANADA
TEL. (450) 477-3102 & (888) 452-6382 WWW.AMETASOLUTION.COM		
Emergency telephone number/restriction on use   Car		n use Canada – CANUTEC 24 hour number 613-996-6666

#### Section 2. Hazard identification

## Classification of hazardous product (name of the category or subcategory of the hazard class)

Extremely flammable aerosol (Category 1)

Gas under pressure (compressed gas)

Specific target organ toxicity – single exposure (Category 3), Central nervous system

Reproductive toxicity (Category 2)

Hazardous to the aquatic environment - Chronic (Category 3)

## Information elements (symbols, signal words, hazard statements and precautionary statements of the category/subcategory)









#### Danger

H222 Extremely flammable aerosol.

H229 Pressurized container: may burst if heated.

H280 Contains gas under pressure; may explode if heated.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H412 Harmful to aquatic life with long lasting effects.

\*\*\* May displace oxygen and cause rapid suffocation. P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a doctor if you feel unwell. P308 + P313 IF exposed or concerned: Get medical attention. P391 Collect spillage. P410+P412+P403+P233 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated area. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other hazards known	Simple Asphyxiants (Category 1)	A gas that is a simple asphyxiant***

Section 3. Composition/information on ingredients		
Chemical name (common name/synonyms)	CAS number or other	Concentration (%)*
Butane	106-97-8	25-50
Propane	74-98-6	10-25
Pentane	109-66-0	2.5-10
Hydrocarbons, C6, isoalkanes	64742-49-0	2.5-10
Carbon	7440-44-0	2.5-10
Hydrocarbons, C6-C7, isoalkanes, cyclics	EC 926-605-8	2.5-10
Isobutane	75-28-5	< 2.5
Aluminium	7429-90-5	< 2.5
Propylene carbonate	108-32-7	< 2.5
n-Hexane	110-54-3	< 1
Cyclohexane	110-82-7	< 1
Chromium	7440-47-3	< 1
Hydrocarbons, C9, aromatic	64742-95-6	< 1
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	68457-79-4	< 1
All ingredients are listed according	to OSHA (29 CFR).	•

\* Statement - This safety data sheet provides concentration range(s) instead of the actual concentration(s) considered trade secret(s).



Section 4. First-aid measures		
Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.	
Ingestion	IF SWALLOWED: Immediately call a doctor. DO NOT INDUCE VOMITING. NEVER give anything by mouth if victim is	
	rapidly losing consciousness, or is unconscious or convulsing. Rinse mouth thoroughly with water. Have victim drink two	
	glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.	
Skin contact	IF ON SKIN, Wash with plenty of water for several minutes (5-10). If skin irritation occurs: Get medical attention.	
Eye contact	IF IN EYES, Rinse cautiously with water for several minutes (5-10). Remove contact lenses, if present and easy to do.	
	Continue rinsing. If eye irritation persists: Get medical attention.	
Most important symptoms and effects (acute or delayed)  May cause drowsiness or dizziness.		
Indication of im	mediate medical attention/special treatment In all cases, call a doctor. Do not forget this document.	

# **Section 5. Fire-fighting measures**

## **Specific hazards of the hazardous product (hazardous combustion products)**

Carbon oxides and other irritant/toxic gases and fumes.

#### Suitable and unsuitable extinguishing media

In case of fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish.

#### Special protective equipment and precautions for fire-fighters

During a fire, irritating/toxic smoke and fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece. Shield personnel to protect from venting, rupturing or bursting cans. Move containers from fire area if it can be done without risk. Water spray may be useful in cooling equipment and cans exposed to heat and flame.

# Section 6. Accidental release measures

## Personal precautions, protective equipment and emergency procedures

Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment (See Section 8).

## Methods and materials for containment and cleaning up

Avoid release to the environment. Collect spillage. Ventilate area of release. Stop the leak if it can be done safely. Contain and absorb any spilled liquid concentrate with inert absorbent material, then place material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.

#### Section 7. Handling and storage

## **Precautions for safe handling**

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash hands/nails/face thoroughly after handling. Wear gloves/protective clothing/eye protection/face protection.

Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to Section 8.

## Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks.

# Section 8. Exposure controls/Personal protection

# Control parameters (biological limit values or exposure limit values and source of those values)

Exposure limits: CAS 74-98-6 & 75-28-5 & 106-97-8 – ACGIH – TLV-TWA (STEL) and/or PEL-TWA 1000 ppm; CAS 110-82-7 – ACGIH – TLV-TWA 100 ppm; CAS 7429-90-5 – ACGIH – TLV-TWA 1 mg/m³ & PEL-TWA 1 mg/m³; CAS 110-54-3 – ACGIH – TLV-TWA (STEL) and/or PEL-TWA 50 ppm; CAS 7440-47-3 – ACGIH – TLV-TWA 0.5 mg/m³ & PEL-TWA 1 mg/m³; CAS 109-66-0 – ACGIH – TLV-TWA 600 ppm & PEL-TWA 600 ppm;

#### Appropriate engineering controls

Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

## Individual protection measures/personal protective equipment

Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits are unknown. Chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact, must be worn during all handling operations. Wear protective chemical splash goggles to prevent mists from entering the eyes. Wash hands/nails/face thoroughly after handling. Do not eat, drink or smoke when using this product. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use.



Section 9. Physical and chemical properties			
Appearance, physical state/colour Grey viscous liquid (aerosol)	Vapour pressure Not available		
Odour Petroleum	Vapour density Heavier than air		
Odour threshold Not available	<b>Relative density</b> 0.718 g/cm <sup>3</sup> @ 20°C		
pH Not available	Solubility Insoluble		
Melting/freezing point Not available	Partition coefficient - n-octanol/water Not available		
Initial boiling point/range Not available	Auto-ignition temperature 250°C (liquid)		
Flash point Not available	<b>Decomposition temperature</b> Not available		
Evaporation rate Not available	Viscosity $> 20.5 \text{ mm}^2/\text{s} @ 40^{\circ}\text{C}$		
Flammability (solids and gases)   Extremely flammable aerosol	VOC Not available		
Upper and lower flammability/explosive limits   0.8 % - 10.9 %	Other None known		

#### Section 10. Stability and reactivity

#### Reactivity

Does not react under the recommended storage and handling conditions prescribed.

#### Chemical stability

Stable under the recommended storage and handling conditions prescribed.

#### Possibility of hazardous reactions

Accumulation of flammable if product is heated. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### Conditions to avoid (static discharge, shock or vibration)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

## **Incompatible materials**

Oxidizing materials; etc.

## Hazardous decomposition products

None known

## Section 11. Toxicological information

#### Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact)

May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May displace oxygen and cause rapid suffocation.

## Symptoms related to the physical, chemical and toxicological characteristics

Skin irritation, redness, stinging, pain; Eye irritation, redness, tearing; Respiratory tract irritation, coughing, shortness of breath, dizziness, drowsiness, nausea and headaches.

# Delayed and immediate effects (chronic effects from short-term and long-term exposure)

Skin Sensitization – No data available;

Respiratory Sensitization – No data available;

Germ Cell Mutagenicity – No data available:

Carcinogenicity – No ingredient listed by IARC, ACGIH, NTP or OSHA;

Reproductive Toxicity – Possible;

Specific Target Organ Toxicity — Single Exposure – Central nervous system; Specific Target Organ Toxicity — Repeated Exposure – No data available;

Aspiration Hazard – No data available;

Health Hazards Not Otherwise Classified - No data available.

# Numerical measures of toxicity (ATE; LD<sub>50</sub> & LC<sub>50</sub>)

CAS 75-28-5 & 106-97-8 LC<sub>50</sub> 658000 mg/m<sup>3</sup> 4 hrs (rat); CAS 110-82-7 LD<sub>50</sub> Oral - Rat – 12705 mg/kg & LC<sub>50</sub> - Rat – 34000 mg/m<sup>3</sup> 4H; CAS 110-54-3 LD<sub>50</sub> Oral - Rat - 25 g/kg & LC<sub>50</sub> - Rat - 48000 ppm 4H; CAS 108-32-7 LD<sub>50</sub> Oral - Rat - 29100 mg/kg; CAS 109-66-0 LD<sub>50</sub> Oral - Rat - > 2 g/kg & LC<sub>50</sub> - Rat - 364 mg/m<sup>3</sup> 4H;

ATE not available in this document.

#### **Section 12. Ecological information Ecotoxicity (aquatic and terrestrial information)** No data available for this product. CAS 64742-95-6 EC50/48h 3.2 mg/L (Daphnia) Persistence and degradability No data available for this product. **Bioaccumulative potential** No data available for this product. Mobility in soil No data available for this product. **Other adverse effects** Harmful to aquatic life with long lasting effects. Section 13. Disposal considerations Information on safe handling for disposal/methods of disposal/contaminated packaging Dispose of contents/container into safe container in accordance with local, regional or national regulations.



Section 14. Transport information

UN number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations

UN1950; AEROSOLS; CLASS 2.1

UN number; Proper shipping name; Class(es); Packing group (PG) of the 49 CFR (USA)

UN1950; AEROSOLS; CLASS 2.1

UN number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime)

UN1950; AEROSOLS; CLASS 2.1

UN number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air)

UN1950; AEROSOLS, FLAMMABLE; CLASS 2.1

Special precautions (transport/conveyance) May also be shipped as a LIMITED QUANTITY in accordance with TDG.

**Environmental hazards (IMDG or other)** None

Bulk transport (usually more than 450 L in capacity) Not possible

**Section 15. Regulatory information** 

Safety/health Canadian regulations specifics

Refer to Section 2 for the appropriate classification. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and of the United States OSHA (29 CFR).

Environmental Canadian regulations specifics | Refer to Section 3 for ingredient(s) of the DSL

Safety/health/environmental outside regulations specifics

United States OSHA information: This product is regulated according to OSHA (29 CFR).

United States EPA (Environmental Protection Agency) information: 40 CFR Refer to the ingredients listed in Section 3 & Sections 12; 13 & 14. United States TCSA information: Refer to the ingredients listed in Section 3.

National Fire Protection Association (NFPA):

HEALTH: 1 FLAMMABILITY: 4 INSTABILITY: 1 SPECIAL HAZARDS: Refer to Section 2 & 3.

HAZARD SCALE: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

California Proposition 65: WARNING This product contains n-Hexane (CAS 110-54-3) known to the State of California to cause cancer or other

reproductive harm.

## **Section 16. Other information**

Date of the latest revision of the safety data sheet		st revision of the safety data sheet	DATE: 2025-02-25
	References	Safety Data Sheets from manufactur	rer/supplier & from Canadian Centre for Occupational Health and Safety, CCOHS.

Teres essential	Safety Band Shoets from managerater, supplied to from Sanagram Construction Street, supplied to from Sanagram and Safety, Seconds.
Abbreviations	
ACGIH	American Conference of Governmental Industrial Hygienists

ATE Acute toxicity estimate
CAS Chemical Abstract Service
DSL Domestic Substance List

IARC International Agency for Research on Cancer
IATA International Air Transport Association
IMDG International Maritime Dangerous Goods Code

LC Lethal concentration LD Lethal Dosage

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program (U.S.A.)

OSHA Occupational Safety and Health Administration (U.S.A.)

PEL Permissible Exposure Limit STEL Short-term Exposure Limit

TDG Transport of dangerous goods in Canada

TLV Threshold Limit Value
TSCA Toxic Substances Control Act
TWA Time Weighted Average

WHMIS Workplace Hazardous Materials Information System

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.