

# PROTECTION CORROSION AEROSOL 70-95

**Metaflux®**  
Technical Data Sheet

## DESCRIPTION:

70-95 Metaflux Rust Protection Wax is designed to provide maximum and long-lasting corrosion protection. Our product delivers an **\*\*ultra-thick layer\*\*** in a single application, engineered to withstand the most demanding conditions. With its advanced formula, it penetrates deeply into metals and hollow bodies, even reaching under moisture to create a time-resistant protective barrier. **Tested for salt spray resistance according to DIN 50021 for over 1000 hours**, our product repels water, withstands salts and chemicals, and uses a capillary effect to ensure optimal coverage of metal surfaces, even in the smallest crevices.

This synthetic product is ideal for protecting and maintaining vehicle bodies and metal parts, making it an excellent post-preservation solution for vehicles. Its unique formula ensures exceptional adhesion to all types of metals while offering a permanently elastic protective film. The product's transparent tint preserves the natural appearance of metal surfaces while providing a highly effective anti-corrosion barrier. 70-95 Metaflux Rust Protection Wax dries quickly and is the preferred solution for extending the lifespan of metal parts in the most corrosive environments, offering peace of mind and durable performance.

## USE DIRECTIVES:

Eliminate all oil, rust and dirt from surfaces with Metaflux 70-15. Shake well before use. Spray a thin layer over the parts to be lubricated at a distance of 25 cm. Permanent elastic protective film for metal surfaces, ideal for long-term storage of molds and tools, or for overseas shipment of parts or machinery. Multiple layers can be applied for increased protection; allow each layer to dry before applying the next (approximate drying time: 70 minutes). Shake the aerosol can and spray on pre-cleaned surfaces. For extreme conditions, the application can be repeated multiple times (allow drying time in between). Can be removed with 75-17 SPRAY DETERGENT CITRUS METAFLUX.

Pressurized container: protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash hands/nails/face thoroughly after handling. Wear gloves/protective clothing/eye protection/face protection. Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials. Keep containers closed when not in use. Empty containers are always dangerous.

## PROPERTIES AND ADVANTAGES:

- Ultra-thick layer in a single application
- Waterproofs and ensures effective sealing
- Synthetic
- Water-repellent
- Resistant to salt and chemicals
- With capillary action
- Excellent adhesion to all metals
- Permanently elastic protective film
- Excellent penetration capacity, even reaching the smallest spaces
- Quick drying
- Salt spray test per DIN 50021: > 1000 hours



Content	Type	Art.-No	Box
400ML	SPRAY	70-95	12

1392, Avenue de la gare Mascouche (QC) Canada, J7K 2Z2

1-(888) 452-6382 (450) 477-3102 1-(450) 477-6664

www.ametasolution.com info@ametasolution.com



**AMETA**  
SOLUTION.COM