



PRODUCT IDENTIFIER – Porta 79-02 Industry Cleaner Spray DATE & VERSION – DECEMBER 17, 2024 VERSION 01

SAFETY DATA SHEET (SDS)

Section 2. Hazard identification Classification of hazardous product (name of the category or subcategory of the hazard class)

Extremely flammable aerosol (Category 1)

Skin irritation (Category 2)

Eye irritation (Category 2A)

Aspiration hazard (Category 1)

Specific target organ toxicity – single exposure (Category 3)

Reproductive toxicity (Category 2)

Hazardous to the aquatic environment – Chronic (Category 2)

Information elements (symbols, signal words, hazard statements and precautionary statements of the category/subcategory)









Danger

H222 Extremely flammable aerosol.

H229 Pressurized container: may burst if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H411 Toxic to aquatic life with long lasting effects.

*** May displace oxygen and cause rapid suffocation. P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash hands/nails/face thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear gloves/protective clothing/eye protection/face protection. P301 + P310 IF SWALLOWED: Immediately call a doctor. P331 DO NOT INDUCE VOMITING. P302 + P352 IF ON SKIN: wash with plenty of water. P333 + P313 IF SKIN irritation or rash occurs: Get medical attention. P362 + P364 Take off contaminated clothing and wash it before reuse. P305 + P351 + P338 IF IN EYES, Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical attention. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a doctor if you feel unwell. P308 + P313 IF exposed or concerned: Get medical attention. P391 Collect spillage. P410+P412+P403+P233 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated area. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other hazards known Simple Asphyxiants (Category 1) A gas that is a simple asphyxiant*** Section 3. Composition/information on ingredients Chemical name (common name/synonyms) CAS number or other Concentration (%)* EC 926-605-8/EC 921-024-6/EC 931-254-9 Hydrocarbons C6-C7, mix 30-60 67-63-0 10-30 Isopropanol Ethanol 64-17-5 10-30

 Ethialor
 04-17-5
 10-30

 Carbon dioxide
 124-38-9
 1-5

 n-Hexane
 110-54-3
 1-5

 Cyclohexane
 110-52-7
 < 1</td>

All ingredients are listed according to OSHA (29 CFR).

^{*} Statement - This safety data sheet provides concentration range(s) instead of the actual concentration(s) by weight (except for gases/propellants by volume) considered trade secret(s)



Section 4. First-aid measures				
Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.			
Ingestion	IF SWALLOWED: Immediately call a doctor. DO NOT INDUCE VOMITING. NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Rinse mouth thoroughly with water. Have victim drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.			
Skin contact	IF ON SKIN: wash with plenty of water. (15-20 minutes) IF SKIN irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.			
Eye contact	IF IN EYES, Rinse cautiously with water for several minutes (15-20). Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.			
Most important symptoms and effects (acute or delayed) Causes skin irritation. Causes serious eye irritation.				
Indication of immediate medical attention/special treatment				
Section 5 Fire fighting measures				

Section 5. Fire-fighting measures

Specific hazards of the hazardous product (hazardous combustion products)

Carbon oxides and other irritant/toxic gases and fumes

Suitable and unsuitable extinguishing media

In case of fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish.

Special protective equipment and precautions for fire-fighters

During a fire, irritating/toxic smoke and fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece. Shield personnel to protect from venting, rupturing or bursting cans. Move containers from fire area if it can be done without risk. Water spray may be useful in cooling equipment and cans exposed to heat and flame.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment (See Section 8).

Methods and materials for containment and cleaning up

Avoid release to the environment. Collect spillage. Ventilate area of release. Stop the leak if it can be done safely. Contain and absorb any spilled liquid concentrate with inert absorbent material, then place material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.

Section 7. Handling and storage

Precautions for safe handling

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash hands/nails/face thoroughly after handling. Wear gloves/protective clothing/eye protection/face protection.

Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to Section 8.

Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks.

Section 8. Exposure controls/Personal protection

Control parameters (biological limit values or exposure limit values and source of those values)

Exposure limits: CAS 67-63-0 – ACGIH – TLV-TWA 200 ppm & TLV-STEL 400 ppm & PEL-TWA 400 ppm; CAS 64-17-5 – ACGIH – TLV-TWA 1000 ppm & PEL-TWA 1000 ppm; CAS 110-54-3 – ACGIH – TLV-TWA (STEL) et/ou PEL-TWA 50 ppm; CAS 124-38-9 – ACGIH – TLV-TWA & PEL-TWA 5000 ppm (STEL 30000 ppm); CAS 110-82-7 – ACGIH – TLV-TWA 100 ppm;

Appropriate engineering controls

Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Individual protection measures/personal protective equipment

Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits are unknown. Chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact, must be worn during all handling operations. Wear protective chemical splash goggles to prevent mists from entering the eyes. Wash hands/nails/face thoroughly after handling. Do not eat, drink or smoke when using this product. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use.



Section 9. Physical and chemical properties						
Physical state Aerosol/Liquid	pH Not available					
Colour Clear	Kinematic viscosity Not available					
Odour Characteristic	Solubility Not available					
Melting/freezing point Not available	Partition coefficient - n-octanol/water (log) Not available					
Initial boiling point/ initial/range Not available	Vapour pressure Not available					
Flammability Extremely flammable aerosol	Density/relative density 0.72-0.74 g/cm ³ @ 20°C					
Upper and lower flammability/explosive limits 0.6 % - 13.5 %	Relative vapour density Not available					
Flash point Not available	Particle characteristics Not available					
Auto-ignition temperature 225°C	VOC Not available					
Decomposition temperature Not available	Other None known					
Castion 10 Stability and parativity						

Section 10. Stability and reactivity

Reactivity

Does not react under the recommended storage and handling conditions prescribed.

Chemical stability

Stable under the recommended storage and handling conditions prescribed.

Possibility of hazardous reactions

Accumulation of flammable if product is heated. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding $50 \, ^{\circ}\text{C}/122 \, ^{\circ}\text{F}$.

Conditions to avoid (static discharge, shock or vibration)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Incompatible materials

Oxidizing materials; etc.

Hazardous decomposition products

None known

Section 11. Toxicological information

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact)

May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May displace oxygen and cause rapid suffocation.

Symptoms related to the physical, chemical and toxicological characteristics

Skin irritation, redness, stinging, pain; Eye irritation, redness, tearing; Respiratory tract irritation, coughing, shortness of breath, dizziness, drowsiness, nausea and headaches.

Delayed and immediate effects (chronic effects from short-term and long-term exposure)

Skin Sensitization – No data available;

Respiratory Sensitization - No data available;

Germ Cell Mutagenicity – No data available;

Carcinogenicity - No ingredient listed by IARC, ACGIH, NTP or OSHA;

Reproductive Toxicity - Possible;

Specific Target Organ Toxicity — Single Exposure – Possible;

Specific Target Organ Toxicity — Repeated Exposure – No data available;

Aspiration Hazard - Possible;

Health Hazards Not Otherwise Classified - No data available.

Numerical measures of toxicity (ATE; LD50 & LC50)

 $CAS\ 67-63-0\ LD_{50}\ Oral\ -\ Rat\ -\ 4720\ mg/kg;\ LD_{50}\ Inhalation\ -\ Rat\ -\ 17000\ ppm\ 4hrs;\ LD_{50}\ Dermal\ -\ Rabbit\ -\ 12890\ mg/kg;\ CAS\ 64-17-5\ LD_{50}\ Oral\ -\ Rat\ -\ 25\ g/kg\ \&\ LC_{50}\ -\ Rat\ -\ 48000\ ppm\ 4H;\ CAS\ 110-82-7\ LD_{50}\ Oral\ -\ Rat\ -\ 12705\ mg/kg\ \&\ LC_{50}\ -\ Rat\ -\ 34000\ mg/m^3\ 4H;$

ATE not available in this document.

Saction	17	HCO	OGICO	into	rmatian
Section	14.		IUZICAI	111117	HIIAUVII

Ecotoxicity (aquatic and terrestrial information) No data available for this product.

Persistence and degradability No data available for this product.

Bioaccumulative potential No data available for this product.

Mobility in soil No data available for this product.

Other adverse effects Toxic to aquatic life with long lasting effects.

Section 13. Disposal considerations

Information on safe handling for disposal/methods of disposal/contaminated packaging

Dispose of contents/container into safe container in accordance with local, regional or national regulations.



SOLUTION.COM	DATE & VERSION – DECEMBER 17, 2024 VERSION 01				
Section 14. Transport information					
UN number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations					
UN1950; AEROSOLS; CLASS 2.1					
UN number; Proper shipping name; Class(es); Packing group (PG) of the 49 CFR (USA)					
UN1950; AEROSOLS; CLASS 2.1					
UN number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime)					
UN1950; AEROSOLS; CLASS 2.1; MARINE POLLUTANT					
UN number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air)					
UN1950; AEROSOLS, FLAMMABLE; CLASS 2.1					
Special precautions (transport/conveyance)	May also be shipped as a LIMITED QUANTITY in accordance with TDG.				
Environmental hazards (IMDG or other)	MARINE POLLUTANT				
Section 15. Regulatory information					
Safety/health Canadian regulations specifics	Refer to Section 2 for the appropriate classification. This product has been classified in accordance				
	with the hazard criteria of the Hazardous Products Regulations (HPR) and of the United States				
	OSHA (29 CFR).				
Environmental Canadian regulations specifics					
Safety/health/environmental outside regulations specifics					
United States OSHA information: This product is regulated according to OSHA (29 CFR).					
United States EPA (Environmental Protection Agency) information: 40 CFR Refer to the ingredients listed in Section 3 & Sections 12; 13 & 14.					
United States TCSA information: Refer to the ingredients listed in Section 3.					
National Fire Protection Association (NFPA):					

California Proposition 65: WARNING This product contains n-Hexane (CAS 110-54-3) known to the State of California to cause cancer or other reproductive harm. **Section 16. Other information Date of the latest revision of the safety data sheet** December 17, 2024 version 1 (NSS ENTREPRISE INC.) Corrections Safety Data Sheets from manufacturer/supplier & from Canadian Centre for Occupational Health and Safety, CCOHS References **Abbreviations ACGIH** American Conference of Governmental Industrial Hygienists

SPECIAL HAZARDS: Refer to Section 2 & 3.

INSTABILITY: 1

HAZARD SCALE: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

CAS Chemical Abstract Service DSL Domestic Substance List **IARC** International Agency for Research on Cancer IATA International Air Transport Association **IMDG** International Maritime Dangerous Goods Code LC Lethal concentration LD Lethal Dosage

NIOSH National Institute for Occupational Safety and Health

Acute toxicity estimate

FLAMMABILITY: 4

NTP National Toxicology Program (U.S.A.)

Occupational Safety and Health Administration (U.S.A.) **OSHA** Permissible Exposure Limit PEL

ATE

Short-term Exposure Limit STEL

TDG Transport of dangerous goods in Canada

TLVThreshold Limit Value **TSCA** Toxic Substances Control Act TWA Time Weighted Average

WHMIS Workplace Hazardous Materials Information System

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.